

Top Seal 550 is a cementitious acrylic waterproofing coating.

Large, two-component product. It left the mixer in place of a previously waterproof product.

It is used to improve the water content of facilities: gardens, fountains, water reservoirs, and swimming pools (if tiled).

Insulate balconies and rooms that become humid before use: showers, dishes, and kitchens.

Provides an effective barrier to concrete structures against waterborne salts and atmospheric gases.

Topseal 550 is composed of cement, sand, and chemical additives supplied in powder form, in addition to a liquid component composed of acrylic. Suitable for hot and tropical climates

Caractéristiques:

Water-repellent coating for water retention facilities -

For lining seawater channels. -

Easy to use.

Non-toxic and suitable for contact with drinking water and water reserves.

It offers significant strength on all substrates.

High coverage.

Water resistant.

Moisture-resistant.



Technical Data

Statistical results obtained under standard conditions

Component A:	Gray powder
Component B:	White liquid
Density of the paste:	approximately 1.7 g/cm ³
The thickness of one layer is	1 mm
Applied thicknesses:	2 to 3 mm
Adhesion (flexible system without traffic)	> 0.8 N/mm ²
Adhesion to concrete	> 1.5 N/mm ²
Resistance to positive and negative hydrostatic pressure:	15 bar

Instructions:

Mix Top Seal 550 with an electric mixer. Shake product B well before use. Pour half of product B into a bowl and slowly pour in product A while mixing. Once the mixture is smooth, add the remaining ingredient B and mix vigorously for at least 3 minutes, until smooth and lump-free.

Do not add water or other ingredients; each package must be thoroughly mixed.

Top Seal 550 is applied.

Using a stiff brush, roller, or trowel, it forms a water-resistant coating.

Presentation

20 kg powder + 6 kg liquid.

Store for up to 1 year in its original packaging, protected from weather and moisture.

Note

The instructions in this manual are based on our tests and knowledge, and do not imply any commitment on the part of SARL RITAL or release the consumer from the responsibility of checking and verifying the products for their correct use.

Claims must be accompanied by the original packaging to allow for proper traceability.

SARL RITAL assumes no responsibility, under any circumstances, for the application of its products or construction solutions by the application company or other parties involved in the application and/or execution of the project in question. RITAL's liability is limited exclusively to possible damages directly or exclusively attributable to the products supplied, individually or integrated into systems, due to manufacturing defects.

4kg / 1m²

